

Earth

Traditional collection



heywood
VLOEREN

General product information

Wood Species:	European Oak
Composition:	Engineered (solid on request)
Surface:	Sanded
Finishing:	UV cured (oil)

Dimensions & Gradings

Plank, RL (standard random lengths)

Thickness:	15 mm (5/8") 20 mm (3/4")
Widths:	100 / 120 / 140 / 160 / 180 / 200 / 220 / 240 / 260 / 280 / 300 / 390 mm 3.94" / 4.72" / 5.51" / 6.30" / 7.09" / 7.48" / 7.87" / 8.66" / 9.45" / 10.24" / 11.02" / 11.81" / 15.35"
Lengths:	Random lengths, min. 80% between 1800-2500mm, sometimes up to 3000mm. (max. 20% shorter, between 600-1800mm) Random lengths, min. 80% between 5.9'-8.2', sometimes up to 9.8'. (max. 20% shorter, between 2.0-5.9')
Gradings:	Select, Rustic A, Rustic A/B, Rustic B

Plank, XL & XXL

Thickness:	20 mm (3/4")
XL widths:	220 / 240 / 260 / 280 / 300 / 320 / 340 / 360 / 380 / 400 mm 8.66" / 9.45" / 10.24" / 11.02" / 11.81" / 12.60" / 13.39" / 14.17" / 14.96" / 15.75"
XL lengths:	Random lengths 3000-5500mm. (max. 10% shorter, between 600-3000mm) Random lengths 9.8'-18'. (max. 10% shorter, between 2'-9.8')
XXL widths:	Consult Heywood regarding the possibilities of XXL dimensions
XXL lengths:	Consult Heywood regarding the possibilities of XXL dimensions
Gradings:	Nature, Rustic A, Character, Classic

Herringbone, Chevron (45° or 60°)

Thickness:	15 mm (5/8") 20 mm (3/4")
Dimensions herringbone:	90 x 450 / 100 x 500 / 120 x 600 / 150 x 750 / 180 x 900 / 200 x 1000 mm 3.54 x 17.72" / 3.94 x 19.69" / 4.72 x 23.62" / 5.91 x 29.53" / 7.09 x 35.43" / 7.87 x 39.37"
Dimensions chevron:	90 x 600 / 100 x 600 / 120 x 600 / 150 x 750 / 180 x 900 / 200 x 1000 mm 3.54 x 23.62" / 3.94 x 23.62" / 4.72 x 23.62" / 5.91 x 29.53" / 7.09 x 35.43" / 7.87 x 39.37"
Gradings:	Select, Rustic A, (Rustic A/B from 120mm / 4.72" and wider)

Panels

Thickness:	Consult Heywood regarding the possibilities of panels
Dimensions panels:	Consult Heywood regarding the possibilities of panels
Gradings:	Consult Heywood regarding the possibilities of panels

Miscellaneous

Profile:	Plank: 4 sides tongue & groove Herringbone & Chevron: 4 sides tongue & groove (left & right pcs.)
Bevel options:	Plank: Standard (± 2mm) or micro (± 1mm) bevel on both long sides, head-ends square edged. Additional options (surcharge): 'hand-scraped' bevels, 'antique' bevels, and/or bevel at the ends. Herringbone & Chevron: Standard (± 2mm) or micro (± 1mm) bevel on all four sides. Additional options (surcharge): 'hand-scraped' or 'antique' bevels.
Engineered construction:	15 mm (5/8") : 3,5mm (0.14") hardwood wearlayer glued to 12mm (0.47") multi-layer WBP Birch / Eucalyptus plywood 20 mm (3/4") : 5,5mm (0.22") hardwood wearlayer glued to 15mm (0.59") multi-layer WBP Birch / Eucalyptus plywood
Lamination:	Hotmelt press
Bonding:	Polyurethane reactive hotmelt glue
Moisture content:	8-10% (further dried back on request)
Conformity:	CE (EN 14342 + A1, EN 9239-1 & EN 717-1)
Formaldehyde Emissions:	Class E1 zero emissions

Miscellaneous, cont.

Total thickness tolerance:	+0,2 / -0,2 mm +0.01" / -0.01"
Wearlayer thickness tolerance:	+0,5 / -0,5 mm +0.02" / -0.02"
Width tolerance:	+0,2 / -0,2 mm +0.01" / -0.01"
Length (spring) tolerance:	1 mm bend per L 1000 mm 0.39" bend per L 40" / 3.3ft.
Use:	Indoor
Site conditions:	Keep between 40 - 65% relative humidity & 15°C - 25°C degrees room temperature..
Installation method:	Plank: floating, nailing, or glue-down. Herringbone/Chevron: nailing and/or glue-down. In combination with radiant underfloor heating always glue-down. All Heywood flooring: according to Heywood's installation instructions.
Under Floor Heating:	Suitable for radiant underfloor heating when installed according Heywood's instructions for underfloor heating.

This document has been prepared by Heywood Vloeren B.V.
Subject to typing errors and/or intermediate changes or adjustments.

Heywood Vloeren B.V. reserves the right to change the specifications of this product at any time without obligation to notify third parties.

Manufacturer:

Heywood Vloeren BV
Scheldestraat 30
5347 JD Oss
The Netherlands

T: +31(0)412 65 74 28
E: info@heywoodvloeren.com
I: www.heywoodvloeren.com